

## Datasheet for: 102902



**2/2-solenoid valve,NO,dir. operated, 24V DC, 8W, G1/4, PN0-10bar**

2/2-way solenoid valve brass, NO, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/4, PN - 10bar .  
 Economy series available in three different versions -  
 Directly operated - Combined operation - Pilot-operated For  
 all applications with compressed air, neutral gases or  
 low-viscosity, neutral media.

Type number	MV 1343 G
-------------	-----------

Article number	102902
----------------	--------

EAN/barcode	
-------------	--



4047322158978

Your price	61,85 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	54.0 mm
B	40.0 mm
DN	3.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	140 °C
Max. operating pressure	10 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK321
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/4
Type	2
Valve seat	Brass

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Max. operating pressure</i>	<i>DN</i>	<i>Price</i>
102902	G 1/4	10 bar	3.0	61,85 € / Stk
102900	G 1/8	20 bar	2.0	61,85 € / Stk
102901	G 1/8	14 bar	2.5	61,85 € / Stk
102903	G 1/4	4 bar	4.5	61,85 € / Stk

## More Pictures

