


Datasheet for: 103017



Pressure switch changeover contact design, G 1/8, 0.3-2 bar

Pressure switch changeover contact design, rotating, galvanised steel, Ambient temp. -25°C to 85°C, G 1/8, Setting range 0.3-2 bar . For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Type number	DS 6001
Article number	103017
EAN/barcode	 4047322126489
Your price	55,56 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	2.0 bar
Adjustment range min.	0.3 bar
Applications	Air, hydraulic oil, oil emulsions, water
Electrical connection	Coupling plug Pg 9, DIN 43650
Function	Changeover
Material	Galvanised steel
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK337
Switching frequency	200/min
Switching voltage	250 V
Thread	G 1/8
Type of construction	Spring-loaded diaphragm (NBR)

Variants

Article number	Thread	Adjustment range min.	Adjustment range max.	Price
103017	G 1/8	0.3 bar	2.0 bar	55,56 € / Stk
103018	G 1/8	1.0 bar	10.0 bar	55,56 € / Stk
103019	G 1/8	10.0 bar	70.0 bar	57,55 € / Stk
103020	G 1/4	0.3 bar	2.0 bar	55,56 € / Stk
103021	G 1/4	1.0 bar	10.0 bar	55,56 € / Stk
103022	G 1/4	10.0 bar	70.0 bar	57,55 € / Stk

More Pictures

