


## Datasheet for: 141987

**Pushbutton safety coupling I.D. 11, ISO 6150 C, Sleeve I.D. 19**


Pushbutton safety coupling I.D. 11, ISO 6150 C, Stainless steel, Sleeve I.D.19, Operating press. max. 16 bar, Temp. -20°C to 200°C . High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. These safety couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, manufacturing industry, mining, offshore.

Type number	411.27-ES
Article number	141987
EAN/barcode	 4047322567190
Your price	70,33 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	I.D. 19
DN	11
Flow rate	4500 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel
Length	107.0 mm
Max. operating pressure	16 bar
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK584
Page No. SK	SK068
Plug profile	acc. ISO 6150 C
Pushbutton	Stainless steel
Sealant	FKM
Spring	Stainless steel

Threaded piece  
 Valve  
 a/f

Galvanised steel  
 Brass  
 30 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
141987	I.D. 19	107.0 mm	70,33 € / Stk
141983	I.D. 8	101.0 mm	70,33 € / Stk
141984	I.D. 10	101.0 mm	70,33 € / Stk
141985	I.D. 13	107.0 mm	65,45 € / Stk
141986	I.D. 16	107.0 mm	70,33 € / Stk

## More Pictures

