


Datasheet for: 106426


3/2-way valve man.long rotating lever NC bistable G1/8 valve pos.3

3/2-way valve, manual, Rotating lever, NC, bistable, Connection G 1/8, Operating pre. 1 - 10 bar, Operating temp. -10 °C to 60 °C . 3 valve positions only in conjunction with a second 3/2-way valve. Corresponds to a 5/3-way valve.

Type number	515.504
Article number	106426
EAN/barcode	 4047322205443
Your price	70,56 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Flow rate at 6 bar and Δp 0.5 bar	400 NI/min
Flow rate at 6 bar and Δp 1.0 bar	550 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	1 bar
Min. temperature range	-10 °C
Operation	Bistable
Page No.	HK455
Piston	Aluminium
Sealant	NBR
Spring	Special steel
Symbol	12
Valve body	Aluminium
Valve positions	3

Variants

<i>Article number</i>	<i>Symbol</i>	<i>Operation</i>	<i>Valve positions</i>	<i>Price</i>
106426	12	Bistable	3	70,56 € / Stk
106423	9	Monostable	2	70,56 € / Stk
106424	10	Bistable	2	69,75 € / Stk
106425	11	Monostable	3	70,56 € / Stk

More Pictures

