

Datasheet for: 136338


3-way ball valve, nickel-plated brass, T-hole, Rp 1

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1, DN 25, Operating temp. -15°C to 120°C, PN max. 16 bar . 3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Type number	1086 E
Article number	136338
EAN/barcode	 4047322504232
Your price	61,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	115.0 mm
B	76.0 mm
Ball	Nickel-plated brass (CW617N)
Ball seal	PTFE
DN	25.0
E	19.1 mm
H1	45.0 mm
H2	47.0 mm
Hand lever	Steel with plastic coating
Housing	Nickel-plated brass (CW617N)
L	89.0 mm
Max. operating temperature	120 °C
Min. operating temperature	-15 °C
PN	16 bar
Page No.	HK296
Standard thread	Rp thread acc. to ISO 7-1
Stem seal	PTFE / FKM
Thread	Rp 1
Thread material	Brass
a/f	41 mm

Variants

Article number	Thread	DN	PN	a/f	Price
136338	Rp 1	25.0	16 bar	41 mm	61,96 € / Stk
136340	Rp 1 1/2	40.0	10 bar	55 mm	129,52 € / Stk
136337	Rp 3/4	20.0	16 bar	32 mm	48,44 € / Stk
136339	Rp 1 1/4	32.0	10 bar	50 mm	97,30 € / Stk
136341	Rp 2	50.0	10 bar	70 mm	210,31 € / Stk
136335	Rp 3/8	10.0	25 bar	22 mm	30,18 € / Stk
136336	Rp 1/2	15.0	25 bar	27 mm	34,76 € / Stk
136334	Rp 1/4	8.0	25 bar	22 mm	30,18 € / Stk

More Pictures

