


Datasheet for: 107193


Quick-connect coupling I.D. 5, St. steel 1.4305, G 1/4 ET

Quick-connect coupling I.D. 5, Stainless steel 1.4305, G 1/4 ET, Operating pressure - 35 bar, Temp. -15 °C to 200 °C . One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305, compact with a large bore. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.331
Article number	107193
EAN/barcode	 4047322059619
Your price	70,83 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/4 ET
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Stainless steel 1.4305
Length	38.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK529
Page No. SK	SK015
Retaining ring	Stainless steel
Sealant	FKM
Sleeve	Stainless steel 1.4305
Spring	Stainless steel

Valve body
 a/f

 Stainless steel 1.4305
 17 mm

Variants

Article number	Connection	Length	a/f	Price
107193	G 1/4 ET	38.0 mm	17 mm	70,83 € / Stk
107192	G 1/8 ET	36.0 mm	14 mm	70,83 € / Stk
107194	G 3/8 ET	38.0 mm	19 mm	76,64 € / Stk

More Pictures

