

Datasheet for: 156206


Quick-connect coupling I.D. 2.7, St. steel 1.4305, M5 IT

Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, M5 IT, Operating pressure - 35 bar, Temp. -20 °C to 200 °C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.08/3-ES-E
Article number	156206
EAN/barcode	 4047322625203
Your price	76,86 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel 1.4034
Connection	M5 IT
DN	2.7
Flow rate	120 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel 1.4305
Length	26.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK521
Retaining ring	Stainless steel 1.4310
Sealant	FPM
Sleeve	Stainless steel 1.4305
Spring	Stainless steel 1.4310

Valve body
 a/f

 Stainless steel 1.4305
 9 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>a/f</i>	<i>Price</i>
156206	M5 IT	26.0 mm	9 mm	76,86 € / Stk
156207	G 1/8 IT	28.0 mm	12 mm	81,18 € / Stk

More Pictures

