

Datasheet for: 107066


Stopper valve pneumatically actuated, G 1/4, Plug connector 6/4

Stopper valve pneumatically actuated, G 1/4, Plug connector 6/4, Working pressure max. 10 bar, Medium / ambient temp. max. 70 °C . For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections. Note: Pilot pressure is depending on operating pressure.

Type number	67.014-6
Article number	107066
EAN/barcode	 4047322111539
Your price	62,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

B	58.0 mm
C	28.0 mm
Material	Nickel-plated brass
Max. ambient temperature	70 °C
Max. medium temperature	70 °C
Max. operating pressure	10 bar
Max. pilot pressure	5.0 bar
Min. pilot pressure	1.0 bar
Mounting position	Any, ring piece can be rotated 360° after tighten. the valve
Page No.	HK507
Port 1	G 1/4
Port 2	6 mm
Port 3	4 mm
Sealant	NBR

Variants

Article number	Port 1	Port 2	Price
107066	G 1/4	6 mm	62,91 € / Stk
107065	G 1/8	6 mm	56,15 € / Stk
107067	G 3/8	8 mm	81,77 € / Stk
107068	G 1/2	12 mm	113,57 € / Stk

More Pictures

