


Datasheet for: 107803


GEKA spray nozzle with coupling connector, bright brass, DN 25

GEKA spray nozzle with coupling connector, bright brass, DN 25, Operating pressure max. 40 bar, Med./ambient temp. -10 °C to 90 °C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 714
Article number	107803
EAN/barcode	 4047322389303
Your price	62,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	25.0
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK608
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>Price</i>
107803	25.0	62,97 € / Stk
107802	19.0	28,29 € / Stk
107801	13.0	24,25 € / Stk