


Datasheet for: 142454


**Active charcoal filter »FUTURA-mini« metal container Size 0, G1/4**

Active charcoal filter »FUTURA-mini«, Metal container, 0.005 mg/m<sup>3</sup>, Size 0, G 1/4, Input pressure - 12 bar, Temp. -10°C to 50°C . Activated carbon filters in modern design for compliance with strict compressed air purity requirements. Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m<sup>3</sup> from compressed air and gases.

Type number	FUM 891-M
Article number	142454
EAN/barcode	 4047322556798
Your price	71,41 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	43.0 mm
B	114.0 mm
Bowl	Metal container
C	27.0 mm
Connecting thread	Plastic
Filter element	Activated carbon
Flow rate	470 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar
Housing	PA66 GF60
Max. input pressure	12 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	0.0 bar
Min. temperature range	-10 °C
Page No.	HK015
Residual oil content	0.005 mg/m <sup>3</sup>
Sealant	NBR
Series	FUTURA-mini
Thread	G 1/4

## More Pictures

