

Datasheet for: 103024


Pressure switch changeover contact, Bayonet connector, 1 - 10 bar

Pressure switch changeover contact, Bayonet connector, galvanized steel, Ambient temperature -25 °C to 85 °C, G 1/8, 1 - 10 bar . Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

Type number	DS 4602
Article number	103024
EAN/barcode	 4047322126328
Your price	63,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	10.0 bar
Adjustment range min.	1.0 bar
Electrical connection	Bayonet coupling connector Ø 2.5 mm
Function	Changeover
Material	Galvanized steel
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK338
Switching frequency	200/min
Switching voltage	42 V
Thread	G 1/8
Type of construction	Spring-loaded diaphragm (UR)

Variants

Article number	Thread	Adjustment range min.	Adjustment range max.	Type of construction	Price
103024	G 1/8	1.0 bar	10.0 bar	Spring-loaded diaphragm (UR)	63,02 € / Stk
103023	G 1/8	0.5 bar	2.0 bar	Spring-loaded diaphragm (UR)	63,02 € / Stk
103025	G 1/8	10.0 bar	70.0 bar	Spring-loaded piston	65,82 € / Stk
103026	G 1/4	0.5 bar	2.0 bar	Spring-loaded diaphragm (UR)	63,02 € / Stk
103027	G 1/4	1.0 bar	10.0 bar	Spring-loaded diaphragm (UR)	63,02 € / Stk
103028	G 1/4	10.0 bar	70.0 bar	Spring-loaded piston	65,82 € / Stk

More Pictures

