

Datasheet for: 124818



Mist oiler »variobloc«, PC container, Protec. cage, Size 2, G 1/2

Mist oiler »variobloc«, PC container, protective cage, Size 2, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C . Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VN 24 S
Article number	124818
EAN/barcode	 4047322398206
Your price	71,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	224.0 mm
Bowl	Polycarbonate container with protective cage
C	57.0 mm
Flow rate	4600 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	WEB
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	Price
124818	G 1/2	4600 l/min	2	71,65 € / Stk
124816	G 1/4	3400 l/min	1	50,66 € / Stk
124819	G 3/4	7500 l/min	2	71,65 € / Stk
124817	G 3/8	4400 l/min	1	50,66 € / Stk
124820	G 1	7500 l/min	2	106,13 € / Stk

More Pictures

