

Datasheet for: 100378



Active charcoal filter »multifix-mini«, Metal container, G 1/8

Active charcoal filter »multifix-mini«, metal container, 0.005 mg/m³, G 1/8, Input press. max. 16 bar, Med./ambient temp. max. 60°C. For filtering odours out of compressed air. The activated carbon absorbs the oil vapour molecules contained in the compressed air. A separate filter route prevents activated carbon particles from entering the air flow.

Type number	FA 05 M
Article number	100378
EAN/barcode	 4047322131162
Your price	78,39 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	40.0 mm
B	97.3 mm
Bowl	Metal container
C	12.3 mm
D	85.0 mm
DN	5.0
Filter element	Activated carbon-POM
Flow rate	310 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ_p = 0.2 bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK071
Residual oil content	0.005 mg/m ³
Sealant	NBR
Series	multifix-mini
Thread	G 1/8

More Pictures

