

## Datasheet for: 103038


**Vacuum pressure switch, Special die casting, Flange, -0.85/1 bar**

Vacuum pressure switch, Electrical connection M12x1, Special die casting, Temp. -10 °C to 80 °C, Flange, Setting range -0.85/1 bar . For converting pneumatic to electrical signals. Designed for use in rough vacuum applications (technical vacuum). Universal switch type, suitable as NC, NO or changeover contact. These devices are free from paint-wetting impairment substances (PWIS).

Type number	DS 5902
Article number	103038
EAN/barcode	 4047322212199
Your price	71,98 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	48.0 mm
Adjusting knob	Aluminium, powder-coated
Adjustment range	-0.85 / +1 bar
Applications	Pneumatic applications
B	28.0 mm
Connection	Flange
Diaphragms	NBR
Housing	Special die-cast material
Max. temperature range	80 °C
Min. temperature range	-10 °C
Page No.	HK339
Protection IP	IP 65 (DIN 43650), IP 67 (M12x1)
Sealant	NBR
Switching frequency	200/min.
Switching voltage	max. 250 V AC / 28 V DC

## Variants

Article number	Connection	Price
103038	Flange	71,98 € / Stk
103039	G 1/4	71,98 € / Stk

## More Pictures

