


## Datasheet for: 100692


**Active charcoal filter »variobloc«, PC container, Size 1, G 1/4**

Active charcoal filter »variobloc« with PC container, 0.003 mg/m<sup>3</sup>, Size 1, G 1/4, Input pressure max. 16 bar, Temp. max. 50 °C . Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Type number	VAK 22
Article number	100692
EAN/barcode	 4047322390729
Your price	78,73 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	48.0 mm
Air quality acc. to ISO 8573.1	Class 1 dirt, class 1 oil
B	142.0 mm
Bowl	Polycarbonate container
C	22.0 mm
Flow rate	800 l/min
Flow rate measurement	At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,1 bar
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK107
Residual oil content	0.003 mg/m <sup>3</sup>
Series	variobloc
Size	1
Thread	G 1/4

## Variants

Article number	Thread	Flow rate	Size	Price
100692	G 1/4	800 l/min	1	78,73 € / Stk
100694	G 1/2	1200 l/min	2	117,94 € / Stk
100695	G 3/4	1300 l/min	2	117,94 € / Stk
100693	G 3/8	1000 l/min	1	78,73 € / Stk
100696	G 1	1300 l/min	2	158,14 € / Stk

## More Pictures

