


Datasheet for: 100693


Active charcoal filter »variobloc«, PC container, Size 1, G 3/8

Active charcoal filter »variobloc« with PC container, 0.003 mg/m³, Size 1, G 3/8, Input pressure max. 16 bar, Temp. max. 50 °C . Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

| | |
|----------------|--|
| Type number | VAK 23 |
| Article number | 100693 |
| EAN/barcode |  4047322390897 |
| Your price | 78,73 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------------|--|
| A | 48.0 mm |
| Air quality acc. to ISO 8573.1 | Class 1 dirt, class 1 oil |
| B | 142.0 mm |
| Bowl | Polycarbonate container |
| C | 22.0 mm |
| Flow rate | 1000 l/min |
| Flow rate measurement | At P ₁ = 7 bar and pressure drop Δp = 0,1 bar |
| Max. ambient temperature | 50 °C |
| Max. input pressure | 16 bar |
| Max. medium temperature | 50 °C |
| Page No. | HK107 |
| Residual oil content | 0.003 mg/m ³ |
| Series | variobloc |
| Size | 1 |
| Thread | G 3/8 |

Variants

| Article number | Thread | Flow rate | Size | Price |
|----------------|--------|------------|------|----------------|
| 100693 | G 3/8 | 1000 l/min | 1 | 78,73 € / Stk |
| 100694 | G 1/2 | 1200 l/min | 2 | 117,94 € / Stk |
| 100695 | G 3/4 | 1300 l/min | 2 | 117,94 € / Stk |
| 100692 | G 1/4 | 800 l/min | 1 | 78,73 € / Stk |
| 100696 | G 1 | 1300 l/min | 2 | 158,14 € / Stk |

More Pictures

