

## Datasheet for: 106702


**El. connection (multipole 25-pole, IP 65), Socket IP 67 5 m cable**

Electrical connection (multipole 25-pole, IP 65), Socket IP 67, 25-pole, with 5 m cable . These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

Type number	2269.500
-------------	----------

Article number	106702
----------------	--------

EAN/barcode	 4047322286862
-------------	---

Your price	72,22 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Description	IP 67 connector, 25-pin, with 5 m cable
Manual control	latching
Max. temperature range	60 °C
Min. temperature range	-10 °C
Page No.	HK484
Piloting	Max. 16 (e.g. 16 spring return valves)
Power input	0.6 W per pilot
Protection IP	IP 65

## Variants

<i>Article number</i>	<i>Description</i>	<i>Price</i>
106702	IP 67 connector, 25-pin, with 5 m cable	72,22 € / Stk
106700	IP 67 connector, 25-pin, with 1 m cable	39,41 € / Stk
106701	IP 67 connector, 25-pin, with 2.5 m cable	52,10 € / Stk