

## Datasheet for: 107063



**Stopper valve pneumatically actuated, G 3/8, G 3/8 i., G 1/8 i.**

Stopper valve pneumatically actuated, G 3/8, G 3/8 i., G 1/8 i., Working pressure max. 10 bar, Medium / ambient temp. max. 70 °C . For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections. Note: Pilot pressure is depending on operating pressure.

Type number	66.038-38
-------------	-----------

Article number	107063
----------------	--------

EAN/barcode	
-------------	--



4047322111317

Your price	79,21 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

B	63.0 mm
C	31.0 mm
Material	Nickel-plated brass
Max. ambient temperature	70 °C
Max. medium temperature	70 °C
Max. operating pressure	10 bar
Max. pilot pressure	5.0 bar
Min. pilot pressure	1.0 bar
Mounting position	Any, ring piece can be rotated 360° after tighten. the valve
Page No.	HK507
Port 1	G 3/8
Port 2	G 3/8
Port 3	G 1/8
Sealant	NBR

## Variants

Article number	Port 1	Port 2	Price
107063	G 3/8	G 3/8	79,21 € / Stk
107061	G 1/8	G 1/8	53,35 € / Stk
107062	G 1/4	G 1/4	60,45 € / Stk
107064	G 1/2	G 1/2	120,56 € / Stk

## More Pictures

