

Datasheet for: 135198



Push-in T-fitting, rotating, R 3/8 o., for hose exterior Ø 10 mm

Push-in T-fitting, rotating, R 3/8 o., for hose exterior Ø 10 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	8755.038-10 ES
Article number	135198
EAN/barcode	 4047322494069
Your price	72,48 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	10 mm
L1	48.6 mm
L2	33.7 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK721
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 3/8
Working pressure pulsate a/f	10.0 bar 17 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
135198	R 3/8	10 mm	17 mm	72,48 € / Stk
135190	R 1/8	6 mm	13 mm	44,58 € / Stk
135201	R 1/2	10 mm	22 mm	84,77 € / Stk
135203	R 1/2	14 mm	22 mm	121,28 € / Stk
135200	R 3/8	14 mm	22 mm	141,83 € / Stk
135204	R 1/2	16 mm	24 mm	202,65 € / Stk
135194	R 1/4	8 mm	14 mm	52,82 € / Stk
135193	R 1/4	6 mm	14 mm	46,63 € / Stk
135192	R 1/4	4 mm	14 mm	55,10 € / Stk
135197	R 3/8	8 mm	17 mm	63,90 € / Stk
135199	R 3/8	12 mm	19 mm	102,35 € / Stk
135202	R 1/2	12 mm	22 mm	102,28 € / Stk
135196	R 1/4	12 mm	19 mm	93,24 € / Stk
135191	R 1/8	8 mm	14 mm	51,70 € / Stk
135195	R 1/4	10 mm	16 mm	64,51 € / Stk
135189	R 1/8	4 mm	11 mm	39,36 € / Stk

More Pictures

