

Datasheet for: 103284

Ball valve heavy duty design, Manual lever, ET/ET, R 1 1/4


Ball valve heavy duty design, Manual lever, ET/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, R 1 1/4, PN max. 100 bar . Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Type number	3351.77
-------------	---------

Article number	103284
----------------	--------

EAN/barcode



4047322216265

Your price	72,91 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	150.0 mm
B	96.4 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	32.0
E	21.2 mm
F	21.2 mm
Hand lever	Aluminium, painted black
Housing	Nickel-plated brass
L	122.4 mm
Max. operating temperature	130 °C
Min. operating temperature	-20 °C
PN	100 bar
Page No.	HK273
Standard thread	R thread acc. to DIN EN 10226 (ISO 7-1)
Stem seal	PTFE
Thread	R 1 1/4
Thread material	Brass with a bare metal surface
a/f	50 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103284	R 1 1/4	32.0	100 bar	50 mm	72,91 € / Stk
103280	R 3/8	10.0	100 bar	22 mm	16,32 € / Stk
103286	R 2	50.0	80 bar	70 mm	157,03 € / Stk
103283	R 1	25.0	100 bar	40 mm	49,28 € / Stk
103279	R 1/4	8.0	100 bar	18 mm	13,63 € / Stk
103285	R 1 1/2	40.0	100 bar	57 mm	91,09 € / Stk
103281	R 1/2	15.0	100 bar	27 mm	20,51 € / Stk
103282	R 3/4	20.0	100 bar	33 mm	31,34 € / Stk

More Pictures

