


Datasheet for: 105958



Short stroke cylinder single-acting, Piston Ø 25, Stroke 10, G 1/8

Short stroke cylinder, single-acting, Magnet, Piston Ø 25, Stroke 10, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C. Suitable for installation in limited spaces. Supplied with magnet. Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Type number	3.EMF.25010
Article number	105958
EAN/barcode	 4047322070881
Your price	57,27 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Head	Painted brass
Jacket	C45 steel, hard chrome-plated
Max. temperature range	80 °C
Max. working pressure	10 bar
Min. set pressure	0.6 bar
Min. temperature range	-10 °C
Page No.	HK405
Piston	Synthetic (acetal) resin
Piston gasket	NBR (additional charge for PU and FKM)
Piston rod	C45 steel, hard chrome-plated
Piston rod IT	M5
Piston rod gasket	NBR (additional charge for PU and FKM)
Piston Ø	25 mm
Stroke	10 mm

Variants

Article number	Piston Ø	Stroke	Connection	Piston rod IT	Price
105958	25 mm	10 mm	G 1/8	M5	57,27 € / Stk
105952	12 mm	10 mm	M5	M3	50,80 € / Stk
105953	12 mm	25 mm	M5	M3	51,29 € / Stk
105954	16 mm	10 mm	M5	M5	52,10 € / Stk
105955	16 mm	25 mm	M5	M5	52,70 € / Stk
105956	20 mm	10 mm	M5	M5	54,69 € / Stk
105957	20 mm	25 mm	M5	M5	55,30 € / Stk
105959	25 mm	25 mm	G 1/8	M5	58,34 € / Stk
105960	32 mm	10 mm	G 1/8	M6	64,81 € / Stk
105961	32 mm	25 mm	G 1/8	M6	66,10 € / Stk
105962	40 mm	10 mm	G 1/8	M6	65,51 € / Stk
105963	40 mm	25 mm	G 1/8	M6	66,81 € / Stk
105964	50 mm	25 mm	G 1/8	M8	76,92 € / Stk
105965	63 mm	25 mm	G 1/8	M8	94,81 € / Stk

More Pictures

