


Datasheet for: 106847


3/2-way solenoid valve »lineonline«, Controlled venting NC hose 6

3/2-way solenoid valve »lineonline«, Controlled venting, Hose - hose, for hose Ø 6, NC, 24 V DC, Operating pressure 2.5 - 7 bar . Though small in size, these valves are solenoid-piloted and feature very high performance. Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting. Function corresponds to the normal position of the valve.

Type number	482-6
Article number	106847
EAN/barcode	 4047322092685
Your price	64,33 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	49.0 mm
B	57.5 mm
Body	Technopolymer
Flow rate at 6.3 bar and Δp 1.0 bar	380 NI/min
For pipe Ø	6.0 mm
Function	NC
l	14.6 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	7 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. temperature range	-20 °C
Operating voltage	24 V DC
Page No.	HK496
Pneumatic symbols	On housing
Power input	1.2 W
Sealant	NBR

Variants

Article number	For pipe Ø	Function	Flow rate at 6.3 bar and Δp 1.0 bar	Price
106847	6.0 mm	NC	380 NI/min	64,33 € / Stk
106848	8.0 mm	NC	700 NI/min	64,93 € / Stk
106849	6.0 mm	NO	380 NI/min	64,33 € / Stk
106850	8.0 mm	NO	700 NI/min	64,93 € / Stk

More Pictures

