


Datasheet for: 156617


3/2-way valve »FUTURA«, pneumatically actuated, Size 1, G 3/8

3/2-way valve »FUTURA«, pneumatically actuated, Size 1, G 3/8, Exhaust G 1/4, Input pressure max. 16 bar, Temp. -10 °C to 50 °C . Pneumatic systems or parts of systems can be switched on and off by means of an pneumatic signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FU 928-137
Article number	156617
EAN/barcode	 4047322628082
Your price	64,60 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	52.0 mm
B	85.1 mm
C	52.1 mm
Connecting thread	Material: Die-cast zinc
Exhaust air	G 1/4
Flow rate	2000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Page No.	HK057
Series	FUTURA
Size	1
Thread	G 3/8

Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
156617	G 3/8	G 1/4	2000 l/min	1	64,60 € / Stk
139309	G 3/8	G 1/2	4500 l/min	2	94,70 € / Stk
139310	G 1/2	G 1/2	4500 l/min	2	94,70 € / Stk
156616	G 1/4	G 1/4	2000 l/min	1	64,60 € / Stk
156619	G 1	G 1/2	12500 l/min	4	175,40 € / Stk
156618	G 3/4	G 1/2	12500 l/min	4	175,40 € / Stk

More Pictures

