


Datasheet for: 102820


2/2-way solenoid valve, NC, directly operated, 230 V, 50 - 60 Hz

2/2-way solenoid valve brass, NC, directly operated, 230 V, 50 - 60 Hz, Medium temperature -15 °C to 100 °C, G 1/8, PN - 12 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1224
Article number	102820
EAN/barcode	 4047322157865
Your price	81,70 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	75.0 mm
B	30.0 mm
DN	3.2
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	100 °C
Max. operating pressure	12 bar
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Page No.	HK317
Protection IP	IP65 (with connector socket fitted)
Sealant	FKM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/8
Type	1
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	Min. medium temperature	Max. medium temperature	Sealant	Type	Price
102820	G 1/8	12 bar	-15 °C	100 °C	FKM	1	81,70 € / Stk
102819	G 1/8	12 bar	-25 °C	80 °C	NBR	1	71,04 € / Stk
102821	G 1/4	11 bar	-25 °C	80 °C	NBR	2	82,52 € / Stk
102822	G 1/4	11 bar	-15 °C	100 °C	FKM	2	94,58 € / Stk

More Pictures

