


## Datasheet for: 103733



### Blocking valve pneumat. actuated, single-acting NC, NBR, Rp 3/4

Blocking valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 4.2-8 bar, Rp 3/4 . 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 351.943                                                                                            |
| Article number | 103733                                                                                             |
| EAN/barcode    | <br>4047322079129 |
| Your price     | 130,93 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                            |                                    |
|----------------------------|------------------------------------|
| Connection                 | NAMUR interface, direct: 2 x G 1/8 |
| DN                         | 20.0                               |
| H                          | 63.5 mm                            |
| Housing                    | Nickel-plated brass                |
| Internal parts             | Nickel-plated brass                |
| L                          | 135.0 mm                           |
| Max. operating pressure    | 10 bar                             |
| Max. operating temperature | 80 °C                              |
| Max. pilot pressure        | 8.0 bar                            |
| Min. operating temperature | -20 °C                             |
| Min. pilot pressure        | 4.2 bar                            |
| Mounting position          | Any                                |
| Page No.                   | HK345                              |
| Sealant                    | NBR                                |
| Spring                     | Stainless steel                    |
| Thread                     | Rp 3/4                             |
| Version                    | single-acting - spring to close    |

## Variants

| Article number | Thread   | DN   | Price          |
|----------------|----------|------|----------------|
| 103733         | Rp 3/4   | 20.0 | 130,93 € / Stk |
| 103731         | Rp 3/8   | 10.0 | 104,38 € / Stk |
| 103732         | Rp 1/2   | 15.0 | 115,33 € / Stk |
| 103734         | Rp 1     | 25.0 | 151,67 € / Stk |
| 133395         | Rp 1 1/2 | 40.0 | 273,23 € / Stk |
| 133396         | Rp 2     | 50.0 | 372,63 € / Stk |
| 133394         | Rp 1 1/4 | 32.0 | 219,09 € / Stk |

## More Pictures

