


Datasheet for: 100301


3/2-way valve »FUTURA«, electr. actuated, 230 V AC, Size 1, G 3/8

3/2-way valve »FUTURA«, electr. actuated with solenoid 230 V AC, 50 Hz, Size 1, G 3/8, Exhaust G 1/4, Input pressure 2 - 10 bar . Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FU 928
Article number	100301
EAN/barcode	 4047322191333
Your price	95,39 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	52.0 mm
B	117.8 mm
C	84.8 mm
Connecting thread	Material: Die-cast zinc
Duty cycle	100 %
Electrical connection	Socket coupling EN 175301-803, form C, poles 2+PE
Exhaust air	G 1/4
Flow rate	2000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop $\Delta_p = 1$ bar
Holding power with 50 Hz AC voltage	1.6 VA
Housing	PA66 GF60
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.0 bar
Min. temperature range	-10 °C
Page No.	HK055

Page No. SF	SF019
Pick-up power with 50 Hz AC voltage	2.2 VA
Power input	2.5 Watt with DC voltage
Protection IP	IP 65
Series	FUTURA
Size	1
Thread	G 3/8

Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
100301	G 3/8	G 1/4	2000 l/min	1	95,39 € / Stk
100300	G 1/4	G 1/4	2000 l/min	1	95,39 € / Stk
100302	G 3/8	G 1/2	4500 l/min	2	101,62 € / Stk
100303	G 1/2	G 1/2	4500 l/min	2	101,62 € / Stk
100304	G 3/4	G 1/2	12500 l/min	4	210,98 € / Stk
100305	G 1	G 1/2	12500 l/min	4	210,98 € / Stk

More Pictures

