


Datasheet for: 100541


Active charcoal filter »multifix«, PC container, Size 1, G 1/4

Active charcoal filter »multifix« with PC container and protective cage, 0.005 mg/m³, Size 1, G 1/4, Input pressure max. 16 bar . For filtering odours out of compressed air. The activated carbon absorbs the oil vapour molecules contained in the compressed air. A separate filter route prevents activated carbon particles from entering the air flow.

Type number	FA 11 S
Article number	100541
EAN/barcode	 4047322131216
Your price	96,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	47.8 mm
B	136.8 mm
Bowl	Polycarbonate container with protective cage
C	27.0 mm
D	109.8 mm
DN	6.0
Filter element	Activated carbon-POM
Flow rate	380 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK088
Residual oil content	0.005 mg/m ³
Sealant	NBR
Series	multifix
Size	1
Thread	G 1/4

Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
100541	G 1/4	Die-cast zinc	380 l/min	1	6.0	96,11 € / Stk
100542	G 1/2	Die-cast zinc	1500 l/min	3	15.0	152,24 € / Stk
133150	G 1	Die-cast aluminium	3000 l/min	4	25.0	205,85 € / Stk
133149	G 3/4	Die-cast aluminium	3000 l/min	4	20.0	205,85 € / Stk

More Pictures

