

Datasheet for: 102969


2/2-way sol. valve,AISI 304,NBR,NC, dir. op., 230 V,NPT 1/8

2/2-way sol. valve,AISI 304,NBR,NC,directly op.,230 V,50-60 Hz,med.temp. -25°C - 80°C,amb.temp.-25°C - 55°C,NPT 1/8,PN 0-22 bar . Available versions - Directly operated - Combined operation

Type number MV 100 ES

Article number 102969

EAN/barcode



4047322156363

Your price 96,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	88.0 mm
B	30.0 mm
DN	2.4
Electrical connection	For Pg 11P connector socket acc. to DIN 4400
Function	normally closed (NC)
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	80 °C
Max. operating pressure	22 bar
Min. ambient temperature	-25 °C
Min. medium temperature	-25 °C
Page No.	HK328
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Thread	NPT 1/8
Type	1
Valve seat	Stainless steel 1.4301

Variants

Article number	Thread	Max. operating pressure	Max. medium temperature	DN	Sealant	Price
102969	NPT 1/8	22 bar	80 °C	2.4	NBR	96,22 € / Stk
102970	NPT 1/8	22 bar	100 °C	2.4	FKM	102,08 € / Stk
102971	G 1/4	13 bar	80 °C	4.0	NBR	121,50 € / Stk
102972	G 1/4	13 bar	100 °C	4.0	FKM	132,62 € / Stk

More Pictures

