


Datasheet for: 116370



Service unit 2-part »G-mini«, 5 µm, Size 200, G 1/8, 1.5 - 9 bar

Service unit 2-part »G-mini«, with PC container, 5 µm, Size 200, G 1/8, Input pressure max. 10 bar, Control range 1.5 - 9 bar. Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GCL 05
Article number	116370
EAN/barcode	 4047322308502
Your price	83,00 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	88.0 mm
B	161.0 mm
C	68.0 mm
Condensate drain	Semi-automatic
D	93.0 mm
Filter rating	5.0 µm
Flow rate	500 l/min
Flow rate measurement	At P ₁ = 8 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. medium temperature	70 °C
Min. control range	1.5 bar
Page No.	WEB
Page No. AS	AS024
Sealant	NBR
Series	G-mini
Sight dome	Brass/POM

Size
 Spring bonnet
 Thread

200
 POM
 G 1/8

Variants

Article number	Thread	Price
116370	G 1/8	83,00 € / Stk
116371	G 1/4	83,00 € / Stk

More Pictures

