

Datasheet for: 102973


2/2-way sol. valve,AISI 304,NBR,NC, dir. op.,24 V DC,NPT 1/8

2/2-way sol. valve,AISI 304,NBR,NC,directly op.,24 V DC,med. temp. -25 °C - 80 °C,amb.temp.-25°C - 55°C,NPT 1/8, PN 0-10 bar . Available versions - Directly operated - Combined operation

Type number MV 100 ES-G

Article number 102973

EAN/barcode



4047322156370

Your price 96,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	88.0 mm
B	30.0 mm
DN	2.4
Electrical connection	For Pg 11P connector socket acc. to DIN 4400
Function	normally closed (NC)
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	80 °C
Max. operating pressure	10 bar
Min. ambient temperature	-25 °C
Min. medium temperature	-25 °C
Page No.	HK328
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Thread	NPT 1/8
Type	1
Valve seat	Stainless steel 1.4301

Variants

Article number	Thread	Max. operating pressure	Max. medium temperature	DN	Sealant	Price
102973	NPT 1/8	10 bar	80 °C	2.4	NBR	96,22 € / Stk
102974	NPT 1/8	10 bar	100 °C	2.4	FKM	102,08 € / Stk
102975	G 1/4	3.5 bar	80 °C	4.0	NBR	121,50 € / Stk
102976	G 1/4	3.5 bar	100 °C	4.0	FKM	132,62 € / Stk

More Pictures

