

Datasheet for: 106502


5/2-way valve pneumatic, monostable, Connection G 3/8, DN 13.3

5/2-way valve pneumatic, monostable, Connection G 3/8, DN 13.3, Operating pre. 2.5 to 10 bar, Operating temp. -10°C to 60°C .

Type number 516.302-38

Article number 106502

EAN/barcode



4047322385961

Your price 83,43 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/8
DN	13.3
Flow rate 1	1560 NI/min
Flow rate 2	2150 NI/min
Flow rate measurement 1	Flow rate at 6 bar and Δp 0.5 bar
Flow rate measurement 2	Flow rate at 6 bar and Δp 1.0 bar
Function	5/2
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Monostable
Page No.	HK466
Symbol	27

Variants

Article number	Connection	DN	Flow rate 1	Flow rate 2	Price
106502	G 3/8	13.3	1560 NI/min	2150 NI/min	83,43 € / Stk
106500	G 1/8	5.0	400 NI/min	550 NI/min	36,34 € / Stk
106501	G 1/4	7.5	750 NI/min	1100 NI/min	46,46 € / Stk
106503	G 1/2	15.0	3200 NI/min	4600 NI/min	142,32 € / Stk
106504	G 1/8	5.0	400 NI/min	550 NI/min	40,70 € / Stk
106505	G 1/4	7.5	750 NI/min	1100 NI/min	49,99 € / Stk
106507	G 1/2	15.0	3200 NI/min	4600 NI/min	157,14 € / Stk
106506	G 3/8	13.3	1560 NI/min	2150 NI/min	90,33 € / Stk

More Pictures

