


Datasheet for: 103647


3/2-5/2-way valve, NAMUR, G 1/4 (1), G 1/8 (3+5), 230 V, 50 Hz

3/2-5/2-way valve, NAMUR, Anodised aluminium, Operating temp. -25 °C to 60 °C, 2 - 10 bar, G 1/4 (1), G 1/8 (3+5), 230 V, 50 Hz . Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Type number	551.01
Article number	103647
EAN/barcode	 4047322100441
Your price	111,68 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4 (Port 1), G 1/8 (Port 3 and 5)
DN	6.0
Differential pressure max.	10.0 bar
Differential pressure min.	2.0 bar
Electrical connection	Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580
Flow rate	700 l/min
Housing	Aluminium, anodised black
Manual control	latching
Max. operating temperature	60 °C
Medium	Air, neutral gases (filtered)
Min. operating temperature	-25 °C
Page No.	HK309
Permissible static pressure max.	10 bar
Sealant	NBR and PUR
Voltage	230 V, 50 Hz

Variants

Article number	Voltage	Price
103647	230 V, 50 Hz	111,68 € / Stk
103648	24 V DC	119,86 € / Stk

More Pictures

