

Datasheet for: 133558


**Ball valve with integrated strainer, nickel-plated brass, G 1 1/2**

Ball valve, integrated strainer, nickel-plated brass, Operating temp. -20°C to 100°C, G 1 1/2, DN 36, PN max 20 bar, Mesh size 0.5 . Space and cost saving combination made of ball valve and dirt strainer in one. Replaces the sequence of ball valve - dirt strainer - ball valve and thus reduces installation time and costs. The can be removed easily in locked, pressure released status for cleaning.

Type number 322.08

Article number 133558

EAN/barcode



4047322478878

Your price 83,71 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	158.0 mm
B	80.0 mm
Ball	Chrome-plated brass (CW617N)
Ball seal	PTFE
D	57.5 mm
DN	36.0
E	17.0 mm
Hand lever	Galvanised steel with plastic coating
Housing	Nickel-plated brass (CW617N)
L	97.5 mm
Max. operating temperature	100 °C
Min. operating temperature	-20 °C
PN	20 bar
Page No.	HK275
Screen	Stainless steel, mesh size 0.5 mm
Standard thread	G-thread acc. to DIN EN ISO 228-1
Stem seal	NBR / FKM
Thread	G 1 1/2
Thread material	Nickel-plated brass (CW617N)
a/f 1	54.0 mm
a/f 2	55.0 mm

## Variants

Article number	Thread	DN	PN	a/f 1	a/f 2	Price
133558	G 1 1/2	36.0	20 bar	54.0 mm	55.0 mm	83,71 € / Stk
133559	G 2	46.0	20 bar	66.0 mm	65.0 mm	132,71 € / Stk
133556	G 1	20.0	30 bar	38.0 mm	38.0 mm	32,17 € / Stk
133554	G 1/2	12.0	30 bar	25.0 mm	24.0 mm	16,11 € / Stk
133557	G 1 1/4	28.0	20 bar	48.0 mm	46.0 mm	60,06 € / Stk
133555	G 3/4	16.0	30 bar	31.0 mm	30.0 mm	22,99 € / Stk

## More Pictures

