

Datasheet for: 105586


Corner safety valve, liquids, G 1, Trigger pressure 3 bar

Corner safety valve, for liquids, Red brass, Operating temp. -10 °C to 110 °C, G 1, AF 41, Trigger pressure 3 bar . For non-toxic, non-flammable liquids. No evaporation allowed when blowing off. With diaphragm to protect the spring and with lifting device. Type-tested, TÜV-SV. 749. F

Type number 221.05-3,0

Article number 105586

EAN/barcode



4047322039499

Your price 111,95 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	16.0 bar
Adjustment range min.	1.0 bar
Diaphragms	NBR
H	132.0 mm
Housing	Bronze
Inlet and outlet	Each with female thread acc. to DIN EN ISO 228-1
Internal parts	Brass
L1	36.0 mm
L2	30.0 mm
Max. operating temperature	110 °C
Min. operating temperature	-10 °C
Min. set pressure	3.0 bar
Page No.	HK367
Page No. SF	SF060
Spring	C steel
Spring bonnet	Brass
Thread	G 1
a/f	41 mm

Variants

<i>Article number</i>	<i>Min. set pressure</i>	<i>Price</i>
105586	3.0 bar	111,95 € / Stk
105584	2.0 bar	111,95 € / Stk
105589	4.0 bar	111,95 € / Stk
105591	5.0 bar	111,95 € / Stk
105592	6.0 bar	111,95 € / Stk
105595	7.0 bar	111,95 € / Stk
105580	1.0 bar	111,95 € / Stk
105585	2.5 bar	111,95 € / Stk
105582	1.5 bar	111,95 € / Stk
105583	1.8 bar	111,95 € / Stk
105601	10.0 bar	111,95 € / Stk
105605	12.0 bar	111,95 € / Stk
105607	15.0 bar	111,95 € / Stk
105587	3.2 bar	111,95 € / Stk
105588	3.5 bar	111,95 € / Stk
105596	7.4 bar	111,95 € / Stk
105598	8.0 bar	111,95 € / Stk
105600	9.5 bar	111,95 € / Stk
105581	1.1 bar	111,95 € / Stk
105602	10.3 bar	111,95 € / Stk
105604	11.0 bar	111,95 € / Stk
105606	13.0 bar	111,95 € / Stk
105608	16.0 bar	111,95 € / Stk
105590	4.5 bar	111,95 € / Stk
105593	6.5 bar	111,95 € / Stk
105597	7.5 bar	111,95 € / Stk
105599	8.5 bar	111,95 € / Stk
105594	6.6 bar	111,95 € / Stk
105603	10.5 bar	111,95 € / Stk
117634	5.5 bar	111,95 € / Stk
117633	1.6 bar	111,95 € / Stk
179750	5.2 bar	111,95 € / Stk

More Pictures

