


## Datasheet for: 116416


**Service unit 3-part »G-mini«, 5 µm, Size 200, G 1/4, 1.5 - 9 bar**

Service unit 3-part »G-mini«, with PC container, 5 µm, Size 200, G 1/4, Input pressure max. 10 bar, Control range 1.5 - 9 bar . Three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GFRL 06
Article number	116416
EAN/barcode	 4047322308557
Your price	84,85 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	138.0 mm
B	132.0 mm
C	39.0 mm
Condensate drain	Semi-automatic
D	93.0 mm
Filter rating	5.0 µm
Flow rate	500 l/min
Flow rate measurement	At P <sub>1</sub> = 8 bar, P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. medium temperature	70 °C
Min. control range	1.5 bar
Page No.	WEB
Page No. AS	AS024
Sealant	NBR
Series	G-mini
Sight dome	Brass/POM
Size	200
Spring bonnet	POM

Thread

G 1/4

### Variants

Article number	Thread	Price
116416	G 1/4	84,85 € / Stk
116415	G 1/8	84,85 € / Stk

### More Pictures

