

## Datasheet for: 113298


**High performance silencer G 1 1/4, Supply pressure max. 6 bar**

High performance silencer G 1 1/4, Supply pressure max. 6 bar, Operating temperature -10 °C to 90 °C . Multi-chamber silencers with a high blow-off rate, short exhaust time and excellent silencing effect.

Type number	570-4
Article number	113298
EAN/barcode	 4047322101714
Your price	85,03 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	20.0 mm
B	136.0 mm
C	110.0 mm
Flow rate at 6 bar	31700 l/min
Housing	Galvanized steel housing
Material	Perforated sheet galvanized steel, polyester felt discs
Max. input pressure	6 bar
Max. operating temperature	90 °C
Min. operating temperature	-10 °C
Mounting position	Any
Page No.	HK877
Thread	G 1 1/4

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Flow rate at 6 bar</i>	<i>Price</i>
113298	G 1 1/4	31700 l/min	85,03 € / Stk
113295	G 1/2	13350 l/min	50,87 € / Stk
113296	G 3/4	16700 l/min	57,22 € / Stk
113297	G 1	23350 l/min	82,60 € / Stk
113299	G 1 1/2	53400 l/min	140,96 € / Stk
113300	G 2	56700 l/min	148,93 € / Stk