


Datasheet for: 107107


Quick-connect coupling I.D. 2.7, St. steel 1.4404, M5 ET

Quick-connect coupling I.D. 2.7, Stainless steel 1.4404, M5 ET, Operating pressure - 35 bar, Temp. -15 °C to 200 °C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.08/1-ES
Article number	107107
EAN/barcode	 4047322403863
Your price	97,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel 1.4404
Connection	M5 ET
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Stainless steel 1.4404
Length	26.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	WEB
Page No. SK	SK007
Retaining ring	Stainless steel 1.4404
Sealant	FKM
Sleeve	Stainless steel 1.4404

Spring
 Valve body
 a/f

Stainless steel 1.4404
 Stainless steel 1.4404
 9 mm

Variants

Article number	Connection	Length	a/f	Price
107107	M5 ET	26.0 mm	9 mm	97,93 € / Stk
107108	G 1/8 ET	28.0 mm	11 mm	103,36 € / Stk

More Pictures

