


## Datasheet for: 100394



### Service unit 2-part »multifix-mini«, PC container, Size 0, G 1/8

Service unit 2-part »multifix-mini« with PC container, Size 0, G 1/8, Input pressure max. 12 bar, Control range 0.5 - 10 bar. Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | CL 05 K-HA                                                                                         |
| Article number | 100394                                                                                             |
| EAN/barcode    | <br>4047322345224 |
| Your price     | 85,25 € / Stk                                                                                      |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                             |                                                                         |
|-----------------------------|-------------------------------------------------------------------------|
| A                           | 80.0 mm                                                                 |
| B                           | 165.5 mm                                                                |
| Bowl                        | Polycarbonate container                                                 |
| C                           | 63.0 mm                                                                 |
| Condensate drain            | Semi-automatic                                                          |
| D                           | 102.5 mm                                                                |
| DN                          | 5.0                                                                     |
| Filter rating               | 5.0 $\mu$ m                                                             |
| Flow rate                   | 700 l/min                                                               |
| Flow rate measurement       | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Housing                     | Die-cast zinc                                                           |
| Max. ambient temperature    | 60 °C                                                                   |
| Max. control range          | 10.0 bar                                                                |
| Max. input pressure         | 12 bar                                                                  |
| Max. medium temperature     | 60 °C                                                                   |
| Min. control range          | 0.5 bar                                                                 |
| Page No.                    | HK073                                                                   |
| Pressure gauge display max. | 16.0 bar                                                                |

|                |               |
|----------------|---------------|
| Pressure gauge | 0.0 bar       |
| display min.   |               |
| Sealant        | NBR           |
| Series         | multifix-mini |
| Sight dome     | PA            |
| Spring bonnet  | POM-brass     |
| Thread         | G 1/8         |

## Variants

| Article number | Thread | Price         |
|----------------|--------|---------------|
| 100394         | G 1/8  | 85,25 € / Stk |
| 100395         | G 1/4  | 85,25 € / Stk |

## More Pictures

