

Datasheet for: 135147


Push-in L-fitting, rotating, R 1/4 o., for hose exterior Ø 12 mm

Push-in L-fitting, rotating, R 1/4 o., for hose exterior Ø 12 mm, Working pressure max. 20 bar, Stainless steel 1.4404 . For use in more aggressive environments and corrosive media.

Type number	854.014-12 ES
-------------	---------------

Article number	135147
----------------	--------

EAN/barcode



4047322493550

Your price	97,99 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	12 mm
L1	26.7 mm
L2	35.1 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK720
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 1/4
Working pressure pulsate a/f	10.0 bar 19 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
135147	R 1/4	12 mm	19 mm	97,99 € / Stk
135145	R 1/4	8 mm	14 mm	41,53 € / Stk
135141	R 1/8	6 mm	13 mm	34,76 € / Stk
135149	R 3/8	10 mm	17 mm	75,27 € / Stk
135140	R 1/8	4 mm	11 mm	33,25 € / Stk
135153	R 1/2	12 mm	22 mm	100,97 € / Stk
135155	R 1/2	16 mm	24 mm	133,39 € / Stk
135143	R 1/4	4 mm	14 mm	39,05 € / Stk
135142	R 1/8	8 mm	14 mm	41,64 € / Stk
135151	R 3/8	14 mm	22 mm	117,74 € / Stk
135144	R 1/4	6 mm	14 mm	37,01 € / Stk
135154	R 1/2	14 mm	22 mm	124,45 € / Stk
135152	R 1/2	10 mm	22 mm	77,50 € / Stk
135148	R 3/8	8 mm	17 mm	59,24 € / Stk
135150	R 3/8	12 mm	19 mm	99,11 € / Stk
135146	R 1/4	10 mm	16 mm	54,12 € / Stk

More Pictures

