


Datasheet for: 125320


Microfilter »variobloc«, Metal container, 0.01 µm, Size 1, G 1/4

Microfilter »variobloc«, Metal container incl. viewing tube, 0.01 µm, Size 1, G 1/4, Input pressure max. 20 bar, Temp. max. 50 °C . Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital. As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Type number	VM 22 M
Article number	125320
EAN/barcode	 4047322169004
Your price	98,31 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	48.0 mm
Air quality acc. to ISO 8573.1	Class 1 dirt, class 1 oil
B	155.0 mm
Bowl	Metal container with viewing tube
C	22.0 mm
Efficiency	99.999 %
Filter rating	0.01 µm
Flow rate	370 l/min
Flow rate measurement	At P ₁ = 7 bar and pressure drop Δp = 0,1 bar
Max. ambient temperature	80 °C
Max. input pressure	20 bar
Max. medium temperature	50 °C
Page No.	WEB
Series	variobloc
Size	1
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Size	Price
125320	G 1/4	370 l/min	1	98,31 € / Stk
125321	G 3/8	420 l/min	1	98,31 € / Stk
125322	G 1/2	1000 l/min	2	123,01 € / Stk
125323	G 3/4	1100 l/min	2	123,01 € / Stk
125324	G 1	1100 l/min	2	157,84 € / Stk

More Pictures

