


Datasheet for: 102205



Glycerine pressure gauge, radial bottom, G 1/2, 0-600 bar, Ø 100

Glycerine pressure gauge with metal housing, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0-600 bar, Ø 100. Glycerine-filled bourdon-tube pressure gauge. For measurements in areas with high, dynamic pressure loads and vibration levels. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	736
Article number	102205
EAN/barcode	 4047322115063
Your price	131,98 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.0
Connection	G 1/2
Connection position	radial on bottom
Crimped bezel	CrNi steel
Diameter	100 mm
Front glass	Plexiglass
Housing	Hot-pressed brass
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	CrNi steel 1.4571
Measuring range max. bar	600.0
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK209
Scale graduation in the bar area	10.0 bar

Type

213.40

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
102205	1.0	0.0	600.0	100 mm	G 1/2	131,98 € / Stk
102160	1.6	-1.0	0.0	63 mm	G 1/4	34,36 € / Stk
102161	1.6	-1.0	0.6	63 mm	G 1/4	34,36 € / Stk
102162	1.6	-1.0	1.5	63 mm	G 1/4	34,36 € / Stk
102163	1.6	-1.0	3.0	63 mm	G 1/4	34,36 € / Stk
102164	1.6	-1.0	5.0	63 mm	G 1/4	34,36 € / Stk
102165	1.6	-1.0	9.0	63 mm	G 1/4	34,36 € / Stk
102166	1.6	-1.0	15.0	63 mm	G 1/4	34,36 € / Stk
102167	1.6	0.0	0.6	63 mm	G 1/4	34,36 € / Stk
102168	1.6	0.0	1.0	63 mm	G 1/4	34,36 € / Stk
102169	1.6	0.0	1.6	63 mm	G 1/4	34,36 € / Stk
102170	1.6	0.0	2.5	63 mm	G 1/4	34,36 € / Stk
102171	1.6	0.0	4.0	63 mm	G 1/4	34,36 € / Stk
102172	1.6	0.0	6.0	63 mm	G 1/4	34,36 € / Stk
102173	1.6	0.0	10.0	63 mm	G 1/4	34,36 € / Stk
102174	1.6	0.0	16.0	63 mm	G 1/4	34,36 € / Stk
102175	1.6	0.0	25.0	63 mm	G 1/4	34,36 € / Stk
102176	1.6	0.0	40.0	63 mm	G 1/4	34,36 € / Stk
102177	1.6	0.0	60.0	63 mm	G 1/4	34,36 € / Stk
102178	1.6	0.0	100.0	63 mm	G 1/4	34,36 € / Stk
102179	1.6	0.0	160.0	63 mm	G 1/4	34,36 € / Stk
102180	1.6	0.0	250.0	63 mm	G 1/4	34,36 € / Stk
102181	1.6	0.0	400.0	63 mm	G 1/4	34,36 € / Stk
102182	1.6	0.0	600.0	63 mm	G 1/4	34,36 € / Stk
102183	1.0	-1.0	0.0	100 mm	G 1/2	110,79 € / Stk
102184	1.0	-1.0	0.6	100 mm	G 1/2	110,79 € / Stk
102185	1.0	-1.0	1.5	100 mm	G 1/2	110,79 € / Stk
102186	1.0	-1.0	3.0	100 mm	G 1/2	110,79 € / Stk
102187	1.0	-1.0	5.0	100 mm	G 1/2	110,79 € / Stk
102188	1.0	-1.0	9.0	100 mm	G 1/2	110,79 € / Stk

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
102189	1.0	-1.0	15.0	100 mm	G 1/2	110,79 € / Stk
102190	1.0	0.0	0.6	100 mm	G 1/2	110,79 € / Stk
102191	1.0	0.0	1.0	100 mm	G 1/2	110,79 € / Stk
102192	1.0	0.0	1.6	100 mm	G 1/2	110,79 € / Stk
102193	1.0	0.0	2.5	100 mm	G 1/2	110,79 € / Stk
102194	1.0	0.0	4.0	100 mm	G 1/2	110,79 € / Stk
102195	1.0	0.0	6.0	100 mm	G 1/2	110,79 € / Stk
102196	1.0	0.0	10.0	100 mm	G 1/2	110,79 € / Stk
102197	1.0	0.0	16.0	100 mm	G 1/2	110,79 € / Stk
102198	1.0	0.0	25.0	100 mm	G 1/2	110,79 € / Stk
102199	1.0	0.0	40.0	100 mm	G 1/2	110,79 € / Stk
102200	1.0	0.0	60.0	100 mm	G 1/2	131,98 € / Stk
102201	1.0	0.0	100.0	100 mm	G 1/2	131,98 € / Stk
102202	1.0	0.0	160.0	100 mm	G 1/2	131,98 € / Stk
102203	1.0	0.0	250.0	100 mm	G 1/2	131,98 € / Stk
102204	1.0	0.0	400.0	100 mm	G 1/2	131,98 € / Stk
102206	1.0	0.0	1000.0	100 mm	G 1/2	161,79 € / Stk