


## Datasheet for: 100280


**Pressure switch changeover contact design flangeable, 0.5-10 bar**

Pressure switch changeover contact design flangeable, Plastic, Ambient temp. -10 °C to 60 °C, Setting range 0.5 - 10 bar . Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

|                |  |
|----------------|--|
| Type number    | DS 9410  |
| Article number | 100280   |
| EAN/barcode    | <br>4047322249454 |
| Your price     | 98,97 € / Stk  |

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                          |  |
|--------------------------|--|
| Adjustment range max.    | 10.0 bar   |
| Adjustment range min.    | 0.5 bar  |
| Applications             | Air, neutral gases (lubricated or unlubricated)  |
| Description              | Pressure switches - suitable for flange mounting |
| Electrical connection    | Pg 11P coupling plug acc. to ISO 4400            |
| Function                 | Changeover                                       |
| Material                 | Plastic (PA 61/XT)                               |
| Max. ambient temperature | 60 °C  |
| Min. ambient temperature | -10 °C   |
| Page No.                 | HK335  |
| Protection IP            | IP 65  |
| Switching frequency      | 60 Zyklen/min.                                   |
| Switching voltage        | max. 250 V AC/DC                                 |
| Type of construction     | Spring-loaded diaphragm (NBR)                    |