


## Datasheet for: 101018



### Mist oiler »Standard« with polycarbonate container, Size 3, G 3/4

Mist oiler »Standard« with polycarbonate container, Size 3, G 3/4, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Proportional lubricators, oil can be filled under pressure.

Type number	761 K
Article number	101018
EAN/barcode	 4047322117463
Your price	99,13 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	102.0 mm
Bowl	Polycarbonate container
C	58.0 mm
D	160.0 mm
DN	20.0
Flow rate	9000 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK128
Sealant	NBR
Series	Standard
Sight dome	PA
Size	3
Thread	G 3/4

## Variants

Article number	Thread	Flow rate	Size	DN	Price
101018	G 3/4	9000 l/min	3	20.0	99,13 € / Stk
101014	G 1/4	1200 l/min	1	6.0	35,04 € / Stk
101015	G 3/8	1200 l/min	1	6.0	35,04 € / Stk
101016	G 3/8	2400 l/min	2	10.0	51,34 € / Stk
101017	G 1/2	4000 l/min	3	15.0	56,28 € / Stk
101019	G 1	9000 l/min	3	25.0	98,16 € / Stk
101020	G 1 1/4	9000 l/min	4	40.0	211,30 € / Stk
101021	G 1 1/2	9000 l/min	4	45.0	209,25 € / Stk

## More Pictures

