

Datasheet for: 100406



Switch valve (3/2-way valve) »multifix-mini«, 230 V AC, G 1/4

Switch valve (3/2-way valve) »multifix-mini«, 230 V AC, 50 Hz, G 1/4, Input pressure 2 - 10 bar, Medium / ambient temp. max. 60 °C . Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. 3/2-way type including silencer. When they are switched off, the system is relieved at the same time.

Type number	S 06-2
Article number	100406
EAN/barcode	 4047322165143
Your price	114,66 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	45.0 mm
B	29.0 mm
C	96.0 mm
Duty cycle	100 %
Electrical connection	Device plug PG 9, type B, EN 175301-803
Flow rate	2000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	10 bar
Max. medium temperature	60 °C
Min. input pressure	2.0 bar
Page No.	HK076
Protection IP	IP65 (P 54) acc. to DIN 40050
Sealant	NBR
Series	multifix-mini
Solenoid	230 V AC, 50 Hz
Thread	G 1/4
Vent port	G 1/4

Variants

Article number	Solenoid	Price
100406	230 V AC, 50 Hz	114,66 € / Stk
100407	110 V AC, 50 Hz	114,66 € / Stk
100408	24 V DC	114,66 € / Stk

More Pictures

