


Datasheet for: 100803



Service unit 3-part »Standard-mini« with metal container, G 1/8

Service unit 3-part »Standard-mini«, Metal container, pressure gauge, G 1/8, Input pressure max. 25 bar, Control range 0.5-10 bar. Compact, three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	845.01 M
Article number	100803
EAN/barcode	 4047322121170
Your price	133,12 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	130.0 mm
B	168.7 mm
Bowl	Metal container
C	70.2 mm
Condensate drain	manual
D	98.5 mm
DN	5.0
Filter rating	5.0 μ m
Flow rate	300 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK119
Pressure gauge display max.	16.0 bar

Pressure gauge	0.0 bar
display min.	
Sealant	NBR
Series	Standard-mini
Sight dome	Zinc-glass-NBR
Thread	G 1/8

Variants

Article number	Thread	Price
100803	G 1/8	133,12 € / Stk
100804	G 1/4	133,12 € / Stk

More Pictures

