


Datasheet for: 100581



Service unit 3-part »multifix« with PC container, Size 1, G 1/4

Service unit 3-part »multifix« with polycarbonate container, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar. Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	FRL 11 K-HA
Article number	100581
EAN/barcode	 4047322345422
Your price	114,90 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	137.8 mm
B	192.1 mm
Bowl	Polycarbonate container
C	67.0 mm
Condensate drain	Semi-automatic
D	125.1 mm
DN	6.0
Filter rating	5.0 µm
Flow rate	1100 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK093
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar

Sealant
 Series
 Sight dome
 Size
 Spring bonnet
 Thread

NBR
 multifix
 PA
 1
 POM-brass
 G 1/4

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100581	G 1/4	Die-cast zinc	5.0 μm	1100 l/min	1	6.0	114,90 € / Stk
100585	G 1	Aluminium	40.0 μm	11300 l/min	5	25.0	471,23 € / Stk
100582	G 3/8	Die-cast zinc	5.0 μm	1100 l/min	1	10.0	114,90 € / Stk
100584	G 3/4	Die-cast zinc	5.0 μm	3000 l/min	3	25.0	168,65 € / Stk
100583	G 1/2	Die-cast zinc	5.0 μm	3000 l/min	3	15.0	168,65 € / Stk

More Pictures

