

## Datasheet for: 142178

**End distributor socket, 2 swing safety coupl. I.D.7.2, max12bar**

End distributor socket, 2 swing safety couplings, I.D. 7.2, input G 1/2, Operat. pressure max. 12bar, Ambient temp. -10°C to 50°C. 2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. Available with 2 or 3 pre-assembled, swing safety couplings and 2 inlet thread sizes for input and output threads (Not combinable). All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.



Type number	EVDSCH12-2
Article number	142178
EAN/barcode	 4047322553407
Your price	86,51 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Coupling	2 x swing safety coupling
Height	59.0 mm
Housing	Glass fibre-reinforced plastic
Inlet thread	G 1/2
Max. operating pressure	12 bar
Max. temperature range	50 °C
Max. tightening torque brass thread	12 Nm
Max. tightening torque mounting holes	4 Nm
Min. temperature range	-10 °C
Page No.	HK563
Page No. SK	SK046
Thread material	Brass

Width 165.0 mm

## Variants

Article number	Coupling	Price
142178	2 x swing safety coupling	86,51 € / Stk
142180	3 x swing safety coupling	116,69 € / Stk

## More Pictures

