

## Datasheet for: 103130


**Ball valve standard design, full passage, IT/IT, G 2**

Ball valve standard design, full passage, IT/IT, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 2, DN 50, PN max. 40 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Type number	330.09
Article number	103130
EAN/barcode	 4047322073653
Your price	86,54 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	165.0 mm
B	92.4 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	50.0
E	16.5 mm
F	16.5 mm
Hand lever	Aluminium, painted black
L	109.0 mm
Material	Nickel-plated brass
Max. operating temperature	90 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK269
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
Thread	G 2
Thread material	Brass with a bare metal surface

## Variants

Article number	Thread	DN	Price
103130	G 2	50.0	86,54 € / Stk
103123	G 1/4	8.0	10,75 € / Stk
103124	G 3/8	10.0	10,75 € / Stk
103125	G 1/2	15.0	11,60 € / Stk
103126	G 3/4	20.0	16,08 € / Stk
103127	G 1	25.0	23,41 € / Stk
103128	G 1 1/4	32.0	37,85 € / Stk
103129	G 1 1/2	40.0	56,97 € / Stk
103131	G 2 1/2	65.0	174,90 € / Stk
103132	G 3	80.0	247,32 € / Stk

## More Pictures

