


## Datasheet for: 135155



### Push-in L-fitting, rotating, R 1/2 o., for hose exterior Ø 16 mm

Push-in L-fitting, rotating, R 1/2 o., for hose exterior Ø 16 mm, Working pressure max. 20 bar, Stainless steel 1.4404 .  
 For use in more aggressive environments and corrosive media.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 854.012-16 ES                                                                                      |
| Article number | 135155                                                                                             |
| EAN/barcode    | <br>4047322493635 |
| Your price     | 133,39 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                              |                        |
|------------------------------|------------------------|
| For tube O.D.                | 16 mm                  |
| L1                           | 30.0 mm                |
| L2                           | 43.5 mm                |
| Material                     | Stainless steel 1.4404 |
| Max. medium temperature      | 150 °C                 |
| Max. operating temperature   | 150 °C                 |
| Max. working pressure        | 20 bar                 |
| Min. medium temperature      | -20 °C                 |
| Min. operating temperature   | -20 °C                 |
| Page No.                     | HK720                  |
| Standard thread              | ISO 7-1                |
| Suitable pipe materials      | PVDF, PTFE, PA, PU     |
| Thread                       | R 1/2                  |
| Working pressure pulsate a/f | 10.0 bar<br>24 mm      |

## Variants

| Article number | Thread | For tube O.D. | a/f   | Price          |
|----------------|--------|---------------|-------|----------------|
| 135155         | R 1/2  | 16 mm         | 24 mm | 133,39 € / Stk |
| 135145         | R 1/4  | 8 mm          | 14 mm | 41,53 € / Stk  |
| 135141         | R 1/8  | 6 mm          | 13 mm | 34,76 € / Stk  |
| 135149         | R 3/8  | 10 mm         | 17 mm | 75,27 € / Stk  |
| 135147         | R 1/4  | 12 mm         | 19 mm | 97,99 € / Stk  |
| 135140         | R 1/8  | 4 mm          | 11 mm | 33,25 € / Stk  |
| 135153         | R 1/2  | 12 mm         | 22 mm | 100,97 € / Stk |
| 135143         | R 1/4  | 4 mm          | 14 mm | 39,05 € / Stk  |
| 135142         | R 1/8  | 8 mm          | 14 mm | 41,64 € / Stk  |
| 135151         | R 3/8  | 14 mm         | 22 mm | 117,74 € / Stk |
| 135144         | R 1/4  | 6 mm          | 14 mm | 37,01 € / Stk  |
| 135154         | R 1/2  | 14 mm         | 22 mm | 124,45 € / Stk |
| 135152         | R 1/2  | 10 mm         | 22 mm | 77,50 € / Stk  |
| 135148         | R 3/8  | 8 mm          | 17 mm | 59,24 € / Stk  |
| 135150         | R 3/8  | 12 mm         | 19 mm | 99,11 € / Stk  |
| 135146         | R 1/4  | 10 mm         | 16 mm | 54,12 € / Stk  |

## More Pictures

