


Datasheet for: 116163



5/3-way valve, electropneumatic, »4V« Centre closed, 230 V, 50 Hz

5/3-way valve, electropneumatic, »4V«, Centre closed, G 3/8, 230 V, 50 Hz, Operating pressure 1.5-8 bar, Temp. -20°C to 70°C . 5/3-way pilot valves - Electro-pneumatic -

Type number	517.3105
Article number	116163
EAN/barcode	 4047322310888
Your price	115,23 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/4
Flow rate	950 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Mid-position closed
Page No.	HK469
Page No. AS	AS088
Protection IP	IP 65
Size	300
Symbol	37
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116163	G 3/8	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116164	G 1/2	G 1/2	230 V, 50 Hz	1600 l/min	400	158,29 € / Stk
116154	G 1/4	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116153	G 1/8	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116151	M5	M5	24 V DC	250 l/min	100	101,14 € / Stk
116159	G 1/8	G 1/8	230 V, 50 Hz	400 l/min	100	101,14 € / Stk
116156	G 3/8	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116155	G 1/4	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116152	G 1/8	G 1/8	24 V DC	400 l/min	100	101,14 € / Stk
116157	G 1/2	G 1/2	24 V DC	1600 l/min	400	158,29 € / Stk
116158	M5	M5	230 V, 50 Hz	250 l/min	100	101,14 € / Stk
116160	G 1/8	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116161	G 1/4	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116162	G 1/4	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk

More Pictures

